

OPERATION

MANUAL

Chinese Range



Oberai Equipments

*Plot No 5, Konark Apartment,
Cuttack Road, Opp Falcon House
Bhubaneswar - 751006*

Mob: +91 9776800012 / +91 9776471111

Mob: +91 9437028164 / +91 9776010001

INTRODUCTION

Panel: 16swg SS, Drip Tray: 18 swg Internal SS angle structure, 35 mm X 35mm X 16swg SS Square pipe verticals with hard nylon adjustable bullet fits, Bottom Cross Bracing: 25mmX25mmX16swg SS, cast iron grid, gas burner with pilot ignition and control valves.

Drain pipe connected to floor grain removal ss perforated lid with finger holes faucet – swan neck 450mm long swivel.

PURPOSE OF MANUAL

- FOR PREPARATION OF CHINESE FOODS

PROCEDURE FOR OPERATION

MS GAS PIPELINE INSTALLED JUST BACK OF RANGE OPEN THE RED COLOUR NUT (NEEDLE VALVE) TO PASS THE GAS THROUGH RUBBER PIPE TO RANGE

OPEN THE NEEDLE VALVE THAT ARE IN FRONT OF RANGE , THEN BY LIGHTER THE BURNERS FLAMES OUT

- LIKE THIS PROCESS ON/OFF SUPPLY OF GAS SUPPLY OPERATED
- RED FLOWER NUT BY ROTATING RH SIDE IS GAS ON & LH SIDE IS OFF POSITION
- FOR PILOT LAMP BURNER ONLY SLIGHTLY ROTATE TO RH SIDE AND AS IT THE BURNER FLAMES NO NEED TO ROTATE LH SIDE.